

Yealink

EASY VOIP



Yealink 'business class' IP telephones include an impressive set of standard features across the whole T2 series, including HD Voice, PoE, power supply, headset port, handsfree, auto - provisioning and 2 ethernet ports.

New firmware features:

Enhanced Broadsoft Interop, Action URL/URI, Hot desking, Open VPN, XML browser services, 802.1x support, LDAP

T28P

Network Features

6 x VoIP User Accounts & 6 Line Keys
SIP v1 (RFC2543), v2 (RFC3261)
NAT Traversal: STUN mode
Support VLAN, QoS
IP Assignment: Static/DHCP/PPPoE
In-Band DTMF, Out-of-Band DTMF, SIP Info, Proxy mode and Peer-to-peer SIP link mode
TFTP/DHCP/PPPoE client
Telnet/HTTP server
DNS client, NAT/DHCP server

Voice Features

Wideband Codec: G.722.
Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM VAD, CNG, AEC, PLC, AJB, AGC
IP PBX System Integration
Direct IP call without SIP proxy
Dial number via SIP server
Dial URL via SIP server

Security

Secure RTP
Secure configuration file via AES encryption
Digest authentication using MD5/MD5-sess

Physical Features

TI Titan Chipset
Network Interface: 2xRJ45 10/100M ports
Integrated PoE support
320 x 160 pixels graphical LED with 4-level greyscales
XML customisation of screen
Full-duplex hands-free speakerphone
16 programmable keys
Headset port: RJ9

Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward
Caller ID, Call List, DND, Redial, Flash, 3-way Conference, Speed Dial, Personal Ring Tone, Voicemail, Volume Adjustment, Mute, Dial Plan, Dial-now, Paging, Call Park, Call Pick-up, Distinctive Ringtone, Auto-Answer, Intercom

Config, Upgrade and Usage

Auto-provision: TR069 Optional
Firmware Upgrade: TFTP/Console/Auto provision
Downloadable enterprise phonebook

T20P



2 x VoIP User Accounts & 2 Line Keys
2 x 16 Line LCD

T22P



3 x VoIP User Accounts & 3 Line Keys
3 programmable keys
LCD 132 x 64 pixel with white backlit display
Language customisation support
SMS Function

T26P



3 x VoIP User accounts & 3 Line Keys
13 programmable keys with LED indication
3 indication LED
Busy Lamp Field (BLF) Shared Bridged Appearance (BLA)
Expansion Model Support

EXP 39 Expansion Module



20 physical keys with dual colour LED's.
160 x 320 graphic LCD

EXP 38 Expansion Module



38 programmable keys with LED, creates up to 228 additional programmable extensions when 6 EXT are daisy chained.
Functions for IP PBX - supports speed dial, BLF/BLA, intercom, direct pickup, group pickup, conference, hold, transfer, group, listening, call return, voicemail
Only compatible with T26p & T28P

Yealink

EASY VoIP



T18P 'business class' entry level IP phone

Physical Features

TI TITAN chipset
20 keys including 2 programmable keys
4 feature keys (Mute/Redial/Transfer/Hold)
1xLEDs for power and status indication
1xRJ45 10/100M Ethernet ports
Phone label for speed dialing numbers
Power adapter: AC 100~240V input and DC 5V/1.2A Output
Power over Ethernet (IEEE 802.3af class 1)

Telephony Features

Supports 1 x VoIP User Account, Call Hold, Call Waiting, Call Transfer, Block Anonymous Calls, Hotline, Redial, 2 Speed Dials, Volume Control, Call Mute, Tone scheme, Ringtone Selection (via web), Integrated Voice Response System

Voice Features

Voice Codecs: G.711, G.723.1, G.726, G.729AB, G.722
VAD, CNG, AEC, PLC, AJB, AGC

Network Features

SIP v1(RFC2543), v2(RFC3261)
NAT transverse: STUN mode
IP Assignment: Static/DHCP/PPPoE
In-Band DTMF, Out-of-Band DTMF (RFC2833), SIP Info
Proxy mode and Peer-to-peer SIP link mode
TFTP/DHCP/PPPoE client
DNS client, NAT/DHCP server



VP-2009 'business class' IP video phone

Video Features

Touch screen
7" digital TFT-LCD with 800 x 480 pixels resolution
Rotatable CMOS sensor camera with 300K pixels
Video codec: H.263 and H.264 baseline profile
Picture codec: JPEG, GIF, PNG, BMP
Frame rate up to 30fps -resolution of D1 (720x480) or CIF (352x288)
Bandwidth: 128kbps~1Mbps
Adaptive bandwidth adjustment

Network Features

SIP v1(RFC2543), v2(RFC3261)
NAT transverse: STUN mode
IP assignment: static/DHCP/PPPoE

In-Band DTMF, Out-of-Band DTMF and SIP Info DTMF
Proxy mode & peer-to-peer SIP link mode
TFTP/DHCP/PPPoE client
NAT/DHCP server
HTTP web server, DNS client
SNTP, QoS, VLAN (802.1p/Q)

Voice Features

Voice codec: G.711, G.723.1, G.729AB, G.722 (wideband)
VAD,CNG,AEC, PLC,AJB,AGC
Full-duplex hands-free speakerphone with AEC

Phone Features

4 x VoIP User Accounts
Video and voice call selection
Call forward, Call waiting, Call transfer
Hold, DND, Mute, Auto answer
Dial plan, Dial-now, Speed dial
Caller ID display, Call history
Phonebook, Black list, Group manage
Volume control, Ring tone selection
Wall paper, Screen saver, Sleep
Get date & time manually or automatically
Icon-driven menu, Multi-language



YHS32 - Headset

Ultra noise cancelling headset
Quick disconnect support
330 degree rotatable microphone boom
Ultra light weight (only 50g)
Comfortable and durable
Over-the-head style
Pliable steel headband, ultra flex design
Large size ear pad, padded T-bar
Active Protection safeguards the user from acoustic shock



EHS36 - Wireless Headset Adaptor

Make and receive calls from anywhere
Fully compatible with Plantronics and Jabra
Control your phone through the wireless headset
Plug and play
Connects to T26P and T28P devices



Yealink Certifications



Yealink

EASY VoIP

Yealink (UK) Ltd, Pennine House, Salford Street, Bury, Lancashire, BL9 6YA, United Kingdom
Tel: +44 (0)161 763 2060 Email: sales@yealink.co.uk Web: www.yealink.co.uk

Due to our policy of continuous product improvement, all specifications may be subject to change without prior notice.
SIP-T /V3/Sep2010