

snom

snom

Contact

Snom Technology GmbH
Arosen Allee 66
13407 Berlin, Germany

Tel.: +49 (0)30 39833-0
Fax: +49 (0)30 39833-111
sales@snom.com
www.snom.com



More details
and information on
[snom.com](https://www.snom.com)



Connecting your Business

Product overview



D862



D865



Coming soon
D892M

Display	5 inch swivel IPS display	5 inch swivel IPS display	5 inch swivel IPS display
Wired Interfaces	EHS, 1x USB	EHS, 2x USB	EHS, 2x USB
Ethernet/Switch	2x Gigabit	2x Gigabit	2x Gigabit
Programmable Buttons (LED)	8	10	10
Integrated Wireless Interfaces	-	WiFi, Bluetooth	WiFi, NFC, DECT, Bluetooth



D785/D787/D385N



D735/D335



D717



D713



**Expansion Module
D7C**

	D785/D787/D385N	D735/D335	D717	D713	Expansion Module D7C
Display	4.3 inch TFT colour display	2.7 inch TFT colour display	2.7 inch TFT colour display	2.8 inch TFT colour display	6.8 inch TFT colour display
Wired Interfaces	D785/D385: EHS, USB D787: EHS, 2x USB	EHS, USB	EHS, USB	EHS	USB
Ethernet/Switch	2x Gigabit	2x Gigabit	2x Gigabit	2x Gigabit	-
Programmable Buttons (LED)	D785/D787: 24 multicolour (6 physical) D385N: 48 multicolour (12 physical)	32 multicolour (8 physical)	3 multicolour	4	16
Extension module	●	●	●	○	●
Bluetooth Compatibility	D785 ● D787/D385N ○	○	○	○	○
Built-in WiFi	D787 ● D785/D385N ○	○	○	○	○

○ Expandable via USB dongle.
All desk phones have a 3 year warranty.



New



D140



D150

Display	2.8 inch greyscale display	2.8 inch greyscale display
Wired Interfaces	EHS, USB	EHS, USB
Ethernet/Switch	2x 10/100 Mbit	2x Gigabit
Programmable Buttons (LED)	2	2
Colour	Slate grey	Slate grey

New



M500
DECT base station

- Can be used in single and dual cell mode
- Up to 48 SIP accounts
- Up to 8 simultaneous calls
- 10 handsets per base in single cell mode / 8 handsets per base in dual cell mode
- LDAP + XML Phonebook
- Shared Call Emulation



M58 DECT

- Display: 5 inch
- Wireless Interfaces: DECT, Bluetooth
- Programmable function keys: 8
- Shared Call Emulation
- Compatible with the base station **M500**



M55

- Display: 2.4 inch
- Standby: 240 hours
- Talk time: 19 hours
- Dimensions: 188 x 55 x 35 mm
- Programmable function keys: 6
- Shared Call Emulation
- Compatible with the base station **M500**



M10 SC



M65



M85



M30



M70



M80



M90

	M10 SC	M65	M85	M30	M70	M80	M90
Display	1.8 inch single-colour	2 inch 176 x 220 px TFT	2 inch 176 x 220 px TFT	2 inch 176 x 220 px TFT	2 inch 240 x 320 px TFT	2 inch 240 x 320 px TFT	2 inch 240 x 320 px TFT
Shockproof	○	○	●	○	●	●	●
IP65 Protection Class	○	○	●	○	○	●	●
Standby time	168 hours	250 hours	200 hours	350 hours	200 hours	200 hours	200 hours
Talk time	9 hours	18 hours	17 hours	22 hours	17 hours	17 hours	17 hours
Dimensions	173 x 49 x 27 mm	141 x 48 x 24 mm	152 x 48 x 28 mm	128 x 53 x 25 mm	118 x 46 x 22 mm	122 x 48 x 22 mm	122 x 48 x 22 mm
Alarm button	○	○	●	○	●	●	●
Additional functions	-	Vibration, belt clip, illuminated keypad	Vibration, illuminated keypad, IP65, Bluetooth, three additional alarm functions	Belt clip, illuminated keypad	Robust design, Bluetooth, illuminated keypad	Robust design, Bluetooth, illuminated keypad	Anti-bacterial coating, Bluetooth, illuminated keypad
Compatible with the base stations	M100 SC	M400, M900	M400, M900	M400, M900	M400, M900	M400, M900	M400, M900



M100 SC



M900 / Outdoor



M400

Cell type	Single	Multicell up to 1,000 base stations	Single
Number of handsets supported	10	Up to 4,000	10
Number of simultaneous calls	6	Up to 8 per base	10
Wideband Codec	Codec G.722	Codec G.722	Codec G.722
PoE support	yes	yes	yes
Compatible with devices	M10 SC	M30, M65, M85, M70, M80, M90	M30, M65, M85, M70, M80, M90



A170 DECT Headset

- Weight: 22 g
- DECT: yes
- Audio: Wideband ETSI
- Talk time: up to 6 hours
- Passive noise cancellation: yes



A150 Micro DECT Headset

- Weight: 23 g
- DECT: yes
- Audio: Wideband ETSI
- Talk time: up to 6 hours
- Passive noise cancellation: yes

For multicell operation:



A190 DECT headset

- Weight: 45 g
- DECT: yes
- Audio: Wideband ETSI
- Talk time: up to 7 hours
- Wideband voice transmission
- Compatible with base stations **M400, M900**



A330D/A330M

- Weight: 220 g / 140 g
- USB: yes
- Audio bandwidth: Wideband ETSI
- Frequency: 20 to 20,000 Hz
- Remote control: yes
- Passive noise cancellation: yes



Coming soon
A350M

- Weight: 155 g
- Bluetooth: yes
- Audio bandwidth: Wideband ETSI
- Frequency: 20 to 20,000 Hz
- Remote control: yes
- Passive noise cancellation: yes



Coming soon
A310D / A310M

- Weight: 209 g / 129 g
- Audio bandwidth: Wideband ETSI
- Frequency: 20 to 20,000 Hz
- Remote control: no
- Passive noise cancellation: yes



M9B

- Wireless functions:
Bluetooth Class 2, DECT range up to 50 m, LED display
- Compatibility:
M900, M70, M80, M85, M90
- Installation:
Up to 10 gateways per M900, up to 1,000 gateways per installation

M9T

- Built-in motion sensor
- LED display
- Long battery life thanks to Bluetooth LE





C520

- Two wireless DECT microphones
- Automatic and adaptive echo cancellation
- Expandable with up to three **C52-SP** handsfree devices for large conference calls in up to four separate rooms
- Support for up to two Bluetooth devices

C52-SP

- Connection via DECT to **C520** and with **A230** to Snom desk phones.
- Battery or mains operation
- Up to 12 hours talk time and up to 70 hours Standby



C300

- Bluetooth and USB
- 6 beamshape microphones
- Multicolour LED status indicator
- Large 5,000 mAh battery
- USB output for smartphone connection
- NFC

PA1+

- 6.5 watt Class D amplifier
- 4 controllable outputs
- Announcements via SIP and multicast
- Robust housing
- Wall and ceiling mounting possible

