Panasonic



QUALITY COMMUNICATION. COST-CUTTING CAPABILITY.

PANASONIC KX-TGP600 SMART IP WIRELESS PHONE SYSTEM

When quality is critical and cost reduction a key consideration, Panasonic's new KX-TGP600 Smart IP wireless phone system is the ideal business communication tool. Easy to install and delivering the flexibility and reliability that are the hallmarks of Panasonic SIP technology, it represents a complete mobility solution at a very reasonable price.

There are a wide variety of optional handsets which are compatible with the KX-TGP600. Among those is the KX-TPA60 DECT cordless handset, offering a 1.8" colour LCD with backlight, HD wideband audio (G.722) and 500 phone book address/20 last dialled number memory. There's also the KX-TPA65 wireless desk phone, which offers a significant advantage over 'traditional' desk phones, as its DECT capabilities mean no additional cabling is required when the system is being installed. Through a combination of handsets and wireless desk phones, and repeater units, users can create communication systems that are entirely suited to the different environments in which their businesses operate, from the office out into the field.

Key Features

- Support for eight DECT cordless handsets and simultaneous outside lines
- VoIP support
- 1.8" colour LCD screen
- Noise reduction functionality
- · Lowered total cost of ownership
- Eco mode
- · Compatible with a variety of Panasonic handsets and a repeater to increase coverage

PRODUCT GUIDE AND SPECIFICATIONS



KX-TPA65



KX-UDT121



KX-UDT131

- Some models will be available to limited countries. - The images shown of products display and lamps

are composite images.

- Weights and dimensions are approximate.

Design and specifi cation subject to change without notice.These products may be subject to export control regulations.

Trademarks and registered trademarks:

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Panasonic Corporation is under licence. Other trademarks and trade names are those of their respective owners.

FEATURE		KX-TGP600
FEATURE VolP Support		
Jon Juhi	IETF SIP version 2 (RFC3261 and companion RFCs)	Yes
	BroadWorks	Yes
	Asterisk	Yes
Voice Cod		163
	Wideband	G.722 / G.722.2 (AMR-WB)
	Narrowband	6.711a-law / 6.711µ-law / 6.729a
Network		
	10 / 100 base-T auto MDI / MDIX Ethernet LAN port	1
	IP Stack mode	IPv4, IPv6, IPv4/IPv6 Dual
Security		
	Secure RTP	Yes
	SIPS/SIP-TLS	Yes
Provision	ing	
	HTTP / HTTPS / FTP / TFTP and Local / Remote WEB configuration	Yes
	Disabling provisioning feature of local operation	Yes
QoS Supp	ort	
	DSCP	Yes
	IEEE 802.1q	Yes
		Yes
Keys and	Indicators	
	Status indicator (Base unit)	LED
	LCD (Base unit / Bundled handset KX-TPA60)	No / 1.8 inch colour LCD
RFSysten		
	Wireless interface	DECT
	EU-DECT 1.88GHz - 1.90GHz	Yes
Phone Fe		U. I. 0
	Multiple handsets	Up to 8
	Multiple lines	Up to 8 Narrowband: Talk 8 + Conference 2
	Simultaneous voice calls	Wideband: Talk 4 + Conference 2
	Handset select for receiving calls	Yes
	Handset and number select for making calls	Yes
	Redial	Yes
	Do not disturb	Yes
	Anonymous calls (CLIR)	Yes
	Anonymous call rejection	Yes
	Caller ID (CLIP, CNIP)	Yes
	DTMF dialling during calls	Yes
	Three-way conferencing	Yes
	Call transfer	Yes
	Call hold	Yes
	Call forwarding (Unconditional / User Busy / No Answer)	Yes
	Call waiting	Yes
	Phonebook (KX-TPA60)	Up to 500
	Call log (Incoming / Outgoing / Missed) (KX-TPA60)	20 / 20 / No (Included incoming call log)
	Distinctive ringing	Yes
0.1	Ringtone selection	Yes
Other		
Power sup		
	Base unit	AC Adaptor, PoE (IEEE 802.3af)
Power cer	Charger	AC Adaptor
Power cor		Stand-by: 2.3 W (When connecting LAN interface of 100Base-TX.)
	Base unit	TALK: 2.5 W, Max.: 2.6 W (When using 10 simultaneous voice calls.)
	Charger	Max. 1.6 W
Battery (B	undled handset KX-TPA60)	Stand-by time: Up to 200 hours, Talk time: Up to 11 hours
Operating environment		0 °C - 40 °C (32 °F - 104 °F) / 20 % - 80 % relative air humidity (dry)
Dimensions (W x D x H mm)		
	Base unit	Approx. 118.7 x 45.0 x 88.1
	Bundled handset KX-TPA60	Approx. 47.8 x 25.5 x 153.2
	Charger cradle for KX-TPA60	Approx. 71.6 x 75.4 x 42.9
		Base unit x 1, Handset (KX-TPA60) x 1, AC adaptor x 2
Packing c	ontents	Battery (Ni-MH AAA) x 2, Charger cradle x 1
		LAN cable x 1, Belt clip x 1, Screw for wall hangings x 2

