



FEEL THE WONDER



TG589vac v2

Wireless .11ac
Smart Ultra-Broadband Gateway

TELECOM

DATA

VIDEO

The Technicolor TG589vac v2 is a powerful network-agnostic Digital Home enabler.

■ Next-Gen Wireless Technology for Next-Gen Speeds

Featuring the next-generation IEEE 802.11ac wireless standard for the 5 GHz band, this dual band Wi-Fi solution makes optimal use of the wireless spectrum. With its optimized antenna configuration, the TG589vac v2 enables even higher throughput and better coverage over the much less crowded 5 GHz radio.

At the same time, it guarantees uninterrupted transmission of data services over IEEE 802.11n using the 2.4 GHz band.

■ Flexible & Future-Proof Software Stack

The TG589vac v2 is enriched with Technicolor Homeware, a reliable and managed middleware that offers an open architecture with multiple application environments fit to open up the connected home and deliver an unlimited spectrum of value-added services and applications.

Featuring a platform agnostic architecture, Technicolor Homeware is a fully portable solution that ensures the fastest time to market. Moreover, its modularity and enhanced life cycle management make it easy to add or remove components to or from a software release, while enabling second & third party development.

Leveraging open source, Technicolor Homeware embraces different execution environments and supports current and emerging trends, transforming the gateway into a full-blown app platform.

Features at a Glance

- Integrated VDSL2 modem
- 1 GE WAN port
- AutoWAN sensing™
- 4 GE LAN ports
- Dual-band concurrent Wi-Fi interfaces
 - IEEE 802.11n 2.4 GHz (2x2) with high power (optional)
 - IEEE 802.11ac 5 GHz (3x3)
- 1 highspeed USB 2.0 master port
- Seamless media sharing (UPnP A/V™ and DLNA®)
- Future-proof full service platform
- Enabled to support Wi-Fi Doctor® (sold separately) and Wi-Fi Controller (sold separately)
- Extensive remote management
- Non-service-affecting platform software upgrades (dual bank memory)
- IPv4 & IPv6 enabled
- Designed according to the latest ECO standards



TG589vac v2

Wireless .11ac

Smart Ultra-Broadband Gateway

■ Best-In-Class Ultra Broadband

The accelerating growth of WAN and LAN traffic is pushing operators to look to ultra-high-speed network technologies to solve the bandwidth crunch. VDSL2 combined with Gigabit Ethernet enables extremely high bandwidth and guarantees superior quality in voice, data and video.

A dedicated Gigabit Ethernet WAN port and AutoWAN sensing make the TG589vac v2 the ideal service gateway for deployment in Fiber To The Home (FTTH) scenarios.

Some of the latest performance-enhancing technologies have been added on top, to get the utmost out of existing infrastructures:

- G.vector: effectively cancels the crosstalk noise inherently present in VDSL2 bands. With vectoring, every line in a binder can operate at peak performance, as if there were no other VDSL2 lines in that binder.
- G.inp (“Impulse Noise Protection”): makes sure that no errors occur on the DSL connection, even under extreme conditions, so that high-quality video transmission is guaranteed at all times. It is based on the principle of retransmission.

Furthermore, the latest wireless technologies ensure robust in-home wireless distribution which reduces wiring complexity and provides true mobility without sacrificing Quality of Service (QoS) and Quality of Experience (QoE) or transfer speeds.

■ Highest Security

The TG589vac v2 Stateful Packet Inspection (SPI) firewall guarantees users the ultimate network security level. Through integration with Network Address & Port Translation (NAPT), the firewall leverages all the Application Level Gateways (ALGs) provided in the NAT context to minimize undesired service impacts.

Advanced smart parental controls, security audit services, access logging and monitoring are optionally available for home, hotspot and mobile data network users to create a fully personalized and time-based access control environment, based on individual user profiles and web usage behaviour.

The TG589vac v2 also supports powerful wireless security mechanisms, such as Wi-Fi Protected Access (WPA, WPA2) together with the secure and user friendly Wi-Fi Protected Setup (WPS) connection and configuration mechanism for connecting wireless clients.

In addition, the TG589vac v2 supports multiple wireless networks (mSSID) enabling to set up independent virtual wireless access points, including controlled wireless hotspots. These additional wireless networks allow other wireless users to enjoy high-performance access without any compromise on the integrity of the basic network, thus keeping the original network access limited and secure.

■ Media Sharing

The TG589vac v2 acts as a fully compliant DLNA 1.5 Digital Media Server (DMS) and enables distribution of all content from any device to any device in the home. You can stream music, data, pictures and video from your gateway to devices connected to your wired or wireless home network.

In addition, the TG589vac v2 supports hot plugging of USB hard disk drives, allowing you to simply plug and play devices without the need to switch the gateway off first.

■ Easy to Manage

The TG589vac v2 is completely designed according to the TR-069's TR-098 IGD data model through which the device can be configured remotely by the operator without interrupting the end user's experience.

In addition, the TR-181i2 Device:2 data model is made available to further increase the remote management capabilities towards life cycle management, diagnostics and application management.

■ IPv6 Enabled

With the approaching IPv4 address pool depletion, our products need to be ready for IPv6. Technicolor is a frontrunner in the introduction of IPv6 on its devices, with the TG589vac v2 being enabled for multiple IPv6 field scenarios. Internet Protocol version 6 is the next generation of Internet technologies aiming to effectively support the ever-expanding Internet usage and functionality, and also to address security concerns that exist in an IPv4 environment.

Technicolor aims to introduce IPv6 as smoothly as possible in customer networks. By providing in-depth knowledge of the networking stack, we guide our customers in their transition from IPv4 to IPv6.

■ ECO

Technicolor is committed to offer its customers sustainable products and implements a set of ECO features to reach the best possible environmental performance. In addition to carefully selected plastics and packaging to minimize the ecological footprint, the TG589vac v2 benefits from a unique combination of hardware and software features that reduce power consumption substantially.

TG589vac v2

Wireless .11ac

Smart Ultra-Broadband Gateway

Technical Specifications

Hardware

■ Interfaces WAN	1 RJ-11 DSL line port 1 Ethernet WAN 10/100/1000 Base-T port
■ Interfaces LAN	4-port autosensing 10/100/1000 Base-T auto-MDI/MDI-X Ethernet LAN switch
■ Buttons	1 USB 2.0 master port IEEE 802.11n 2.4 GHz on-board IEEE 802.11ac 5 GHz on-board Info/ECO button Wi-Fi on/off button WPS button Reset button Power button
■ Power input	DC jack
■ Power supply	12 VDC external PSU
■ AC Voltage	100 - 240 VAC, 50 - 60 Hz (switched mode power supply)
■ Dimensions	213 x 34 x 185 mm (8.39 x 1.34 x 7.28 in.)
■ Operating temperature	0° - 40° C (32° - 104° F)
■ Operating humidity	20% - 80%

xDSL modem

■ Supports multi mode standards	
■ ADSL compliancy	ITU-T G.992.1 Annex A, B (G.dmt) ITU-T G.992.2 Annex A, B (G.lite) ITU-T G.994.1 (G.hs) Rates up to 8 Mbps downstream and 1 Mbps upstream
■ ADSL2 compliancy	ITU-T G.992.3 Annex A, B, L (G.dmt.bis) ITU-T G.992.4 Annex A, B, L (G.lite.bis) ITU-T G.998.4 (G.inp) Rates up to 12 Mbps downstream and 1 Mbps upstream
■ ADSL2+ compliancy	ITU-T G.992.5 Annex A, B, M ITU-T G.998.4 (G.inp) Rates up to 24 Mbps downstream and 3 Mbps upstream
■ VDSL2 compliancy	ITU G.993.2 SOS SRA INM ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.inp) Up to VDSL2 profile 17a
■ Dying Gasp (optional)	

Wireless

■ Full dual band concurrent Wi-Fi access points, Wi-Fi certified®	2.4 GHz (2x2) IEEE 802.11n AP 5 GHz (3x3) IEEE 802.11ac AP with IEEE 802.11ac compliant transmit beamforming
■ 2.4 GHz Wi-Fi power	Standard: up to 20dBm (100mW EIRP) High Power (optional): up to 24dBm (250mW EIRP)
■ Wi-Fi Protected Setup (WPS™)	
■ Wi-Fi security levels	WPA2™-Enterprise / WPA™-Enterprise WPA2™-Personal / WPA™-Personal
■ Wi-Fi Multimedia (WMM®) and WMM-Power Save	
■ Up to 4 BSSIDs (virtual AP) support per radio interface	
■ Wireless hotspot capabilities	
■ 2x2 MIMO 2.4 GHz Wi-Fi features	SGi STBC 20/40 MHz coexistence
■ 3x3 MIMO 5 GHz Wi-Fi features	SGi STBC 20/40/80 MHz mode
■ RX/TX switched diversity	
■ Dynamic rate switching for optimal wireless performance	
■ Manual/auto radio channel selection	

Management

■ Customizable user-friendly GUI via HTTP and HTTPS	
■ Web services API for remote access (portal, management, diagnostics, applications,...)	
■ Web-browsing intercept (install/diagnostics/captive portal)	
■ AutoWAN sensing™ (automatic selection and configuration of WAN interfaces)	
■ TR-069 CPE WAN Management Protocol (CWMP)	TR-098 Internet Gateway Device (IGD) data model TR-111 home network device management TR-140 storage service provisioning TR-143 network throughput performance tests and statistical monitoring TR-157a3 Life Cycle Management (LCM) TR-181i2 Device:2 data model
■ Zero-touch autoprovisioning	

Services

■ Open architecture for 3rd party application and UI development	
■ 3G/LTE/4G mobile fall-back WAN connection (through USB adapter)	
■ Wireless hotspot (optional, on request)	Passpoint GRE tunneling EAP Fon
■ Parental control	URL- and (optional) content-based website filtering Time-based access control
■ Printer sharing	IPP LPD
■ Content sharing	Server Message Block (SMB) Samba file server UPnP A/V™ media server and control point DLNA® DMS Metadata support
■ HDD file systems	FAT32, NTFS, ExFAT EXT2, EXT3, EXT4 HFS+

TG589vac v2

Wireless .11ac

Smart Ultra-Broadband Gateway

Technical Specifications

Networking

- Symmetrical NAT with application helpers (ALGs)
- Game and application sharing NAT port maps
- DHCP conditional serving & relay
- DNS server & relay
- IGMPv3 proxy (Fastleave)
- IGMP snooping (full routed)
- DHCP spoofing
- IEEE 802.1q VLAN bridging, multiple bridge instances
- Multicast to unicast translation on Wi-Fi interfaces

IPv6 networking

- IPv4 / IPv6 dual IP stack
- Supported models
 - PPP(oE)(oA)
 - IPoE(oA)
- Transitioning
 - 6rd/6to4/6in4
 - DS-Lite
- Stateful connection tracking
- Stateful inspection firewall
- DHCPv6
 - Stateful/stateless DHCPv6 client
 - Stateless DHCPv6 server
 - Relay
 - Prefix Delegation
- ICMPv6

Quality of Service

- ATM QoS
 - UBR, VBR-nrt, VBR-rt, CBR shaping, queuing and scheduling
 - CLP tagging
- IP QoS
 - Flexible classification (ALG aided)
 - IP rate limiting (two-rate remarking/dropping)
 - DSCP (re)marking
 - Dynamic link fragmentation
- Ethernet QoS
 - Priority or C-VLAN/S-VLAN tagging
 - Ethernet switch port queuing and scheduling
- Wireless QoS
 - WMM (BE, BK, VI, VO access categories) queuing and scheduling

Security

- Stateful Packet Inspection Firewall (SPIF)
- Customizable firewall security levels
- Intrusion detection and prevention
- DeMilitarized Zone (DMZ)
- Multilevel access policy
- Security and service segregation per SSID

Professional Services

To reinforce our extensive portfolio of digital home solutions, Technicolor has a dedicated Professional Services team to make sure that every deployment is a success, from initial provisioning and integration to operations, upgrades, ongoing support and beyond. Our wide array of services spans the entire customer project lifecycle, encompassing:

- Expert consulting
- Software customizations and customer change orders
- Qualified technical support and maintenance
- Seamless system integration
- Efficient repair, refurbishment and recycling
- Warranty extensions on all our products

TECHNICOLOR WORLDWIDE HEADQUARTERS

1-5, rue Jeanne d'Arc - 92130 Issy-les-Moulineaux, France
Tel: +33 (0)1 41 86 50 00 - Fax: +33 (0)1 41 86 58 59

www.technicolor.com

SALES CONTACT

For more information please get in touch with your usual sales representative or use the following email:

contactsales@technicolor.com

ECO design

- ECO mode for more intelligent power saving
- Wi-Fi on/off button
- WMM-Power Save

Package contents

- TG589vac v2
- DSL cable (RJ-11)
- Ethernet cable (RJ-45)
- Power supply unit
- Quick Setup leaflet(s) (optional)
- Safety Instructions & Regulatory Information booklet
- Filter(s) or splitter(s) (optional)

