

Specifications, Weights and Dimensions

- Colour: GM (Charcoal)
- UPC: 735078039323
- Product dimensions (WxDxH):
BS: 155mm x 218mm x 51mm
Corded HS: 210mm x 51mm x 52mm
Corded HS on BS at 46 degree: 155mm x 197mm x 175mm
- Product weight: 0.81 kgs
- Giftbox dimensions (WxDxH):
165mm x 106mm x 225mm
- Giftbox weight: 1.04kgs
- Master pack dimensions (WxDxH):
442mm x 240mm x 185mm
- Master pack weight: 4.12kgs
- Quantity: 4

Interface

- Ethernet ports (10/100m)
- Base power: Class 3 Power over Ethernet (PoE) or optional AC adapter

Display, Keys and Indicators

- 158 x 57 pixels (w x h) LCD resolution
- LCD backlighting (white)
- 3 soft keys
- 7 dedicated feature keys
- 2 programmable feature keys
- 4-way navigational pad
- Message waiting LED indicator

Audio / Voice

- Full-duplex base speakerphone
- HAC receiver
- 2.5 mm corded headset jack
- HD Voice for receiver

Phone Features

- Supports up to 2 SIP account registrations
- Local phonebook up to 1000 entries
- Phonebook import/export
- LDAP/BroadSoft remote phonebook
- Call history up to 200 entries
- Shared Call Appearance (SCA)/Bridged-Line Appearance (BLA)
- Do Not Disturb (DND)
- Busy lamp fields (BLF)
- 3-way local conference
- N-way network conference

- Call barring/blocking (block anonymous/blacklist)
- Dial plan/digit map
- Hotline
- Intercom
- Mute
- Redial
- 10 speed dial entries
- Call transfer: blind/attended
- Call hold
- Call park
- Call pickup
- Call forwarding: per-line basis (busy/always/no answer)
- Call restriction
- Call timer (call duration)
- Caller ID
- Call completion
- Phonebook matching (incoming and outgoing calls)
- Multicast paging
- Multi-language support
- Automatic Call Distribution (ACD)

Customisation

- Soft key configuration
- Programmable hard keys
- Custom startup and idle logo
- Web interface configuration (admin & user)
- Custom base ringer (.WAV)
- XML Browser
- Action URI
- Active URL (CTI support)
- Custom default file

Security

- 802.1x
- 802.1pq
- Phone lock - restricted config, calls and emergency call only
- Transport Layer Security (TLS)
- Mutual authentication (server and client)
- Certificate management (device & applications)
- AES encryption of config file for provisioning (128/64/32/16 bits)
- LLDP-MED

Network

- IPv4 or IPv6 with DHCP/Static/PPPoE
- STUN
- NAT
- RTP, SRTP
- SNTP
- VLAN
- DNS override
- Failover support and server redundancy
- Layer 3 QoS (ToS, Diffserv)

Voice Codec

- G.711 a-law & u-law
- G.722
- G.726
- G.729
- iLBC

Provisioning

- HTTP, HTTPS, FTP, TFTP
- DHCP options: 66, 159, 160
- TR-069
- PnP

Maintenance

- Diagnostic: pcap trace and port mirroring
- Schedule Resync - time and day setting
- Syslog

Compatibility

- BroadSoft® Broadworks
- Asterisk-based platforms

Other

- Optional AC adapter: VSP-ADPT02
- 3-year standard warranty

AC Adapter

- Colour: Black
- Product dimensions (WxDxH):
42.7mm x 49.2mm x 80.8 mm
- Product weight: 87.1g

Contact Us

VTech SIP Phones UK

 www.ukbusinessphones.vtech.com

 (0)1706 694070

 enquiries_ukbusinessphones@vtech.com

NOTE: Features and functionality may vary, depending on SIP service provider and/or SIP phone system platform.

© 2016 VTech Telecommunications Limited. All rights reserved. VTech® is a registered trademark of VTech Holdings Limited. ErisTerminal™ is a trademark of VTech.

