

# ErisTerminal™ SIP High End Feature Deskset

Support for up to 5 SIP lines/accounts with 16 keys that provide 32 programmable functions

## VSP735A

Designed to work overtime for you, the VSP735A SIP comes with Power over Ethernet (PoE) support and dual Ethernet ports for easy, cost-effective installation. Program up to 32 buttons for one-touch access to shared call appearances, busy lamp fields, quick dial keys, paging and more. Manage multiple calls with advanced call handling features and support for up to five SIP lines/accounts. Support for the G.722 wideband codec for HD Audio means you'll enjoy superior voice quality too.



### VSP735A Deskset Features<sup>1</sup>

|   |  |
|---|--|
| 206 × 128 pixels (w × h) backlit display                                      | Call forward, call blocking  |
| Dual Ethernet ports - GigE  | Do Not Disturb (DND)   |
| Power over Ethernet (PoE) support (Class 3)                                   | Call transfer, call park, call pickup                                  |
| Optional power supply PSU735A   | Paging   |
| Supports for up to 5 SIP lines/accounts                                       | 200-name phonebook   |
| 4 configurable soft keys  | 3-way local conference; N-way network conference                       |
| Supports additional VSP601A cordless DECT handset                             | 10 selectable ringtones  |
| 4-way navigational pad  | Call log/list, history, caller ID <sup>2</sup> support                 |
| Automatic call distribution (ACD)   | Intercom, redial   |
| 32 programmable keys (2 pages x 16): feature keys or line appearances         | 10 speed dial entries  |
| Full-duplex speakerphone  | 2.5 mm corded headset jack   |
| Message waiting indicator   | Adjustable volume  |
| Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs           | Failover support and server redundancy                                 |
| SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch | QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq                  |
| Desk or wall-mountable, no extra bracket required                             | Supports auto provisioning, IPv4, DHCP Client, DNS, HTTPS, SNMP Client |
| Supports VSP500A cordless DECT headset  | VTech redirection server support                                       |
| Auto answer   | Supports custom logos  |
| Hold  | Supports custom default file for provisioning                          |
| Mute  | HAC receiver   |
| Busy Lamp Field (BLF)   | Supports customisation via WebUI (user and administrator)              |
| Shared call appearances (SCA)   | 3-year standard warranty   |

### Specifications, weights & dimensions

|   |   |
|---|---|
| Color: GM (Charcoal)  | Giftbox dimensions (WxDxH): 266mm x 110mm x 236mm     |
| Giftbox weight: 1.375kgs  | Master pack dimensions (WxDxH): 282mm x 239mm x 266mm |
| Product dimensions (WxDxH): BS: 239mm x 197mm x 152mm Corded HS: 205mm x 50.5mm x 52.1mm Corded HS on BS: 239mm x 199mm x 170mm | Master pack weight: 3.14kgs                           |
| Product weight: 1.151kgs  | Quantity: 2   |

### Contact Us

VTech SIP Phones UK

 [www.ukbusinessphones.vtech.com](http://www.ukbusinessphones.vtech.com)

 (0)1706 694070

 [enquiries\\_ukbusinessphones@vtech.com](mailto:enquiries_ukbusinessphones@vtech.com)

<sup>1</sup> Features and functionality are subject to change without notice and may vary, depending on SIP service provider and/or SIP phone system.

<sup>2</sup> Use of caller ID features may require a subscription available through your local telephone company.

