

# Yealink MeetingBar A50 Datasheet

## All-in-One Video Collaboration Bar for Medium to Large Rooms

Yealink MeetingBar A50 is an all-in-one video collaboration bar for premium medium-to-large rooms. This product delivers cutting-edge audio and video communication capabilities, powered by advanced AI technology, ensuring crystal-clear sound and ultra-HD visuals. With intelligent full-duplex, IntelliFocus, and video fence, it redefines the video conferencing experience, bringing unparalleled clarity and efficiency to every meeting.

Yealink MeetingBar A50 is compatible with Microsoft's MDEP\*, which enhances security and deployment experiences. This integration provides users with a more secure environment and streamlined deployment processes, contributing to a smoother and safer user experience.

Moreover, Yealink MeetingBar A50 features a direct connection to CTP25, enabling a simplified login process.

This streamlined login experience saves users time and enhances convenience.

In addition, MeetingBar A50 seamlessly supports Microsoft Teams Rooms (MTR), delivering a consistent and efficient experience whether you're using the Android or Windows version. In MTR-W, it is namely MVC S50.

\*Support 3x expansion microphones: Optional






All-in-One Audio &amp; Video Device



IntelliFocus



Triple-eye Camera System (3\*50MP)



4 \* Speakers with Stereo Sound



10m Pick-up Range



AI Noise Cancellation



Video Fence



Android or Windows

## Key Features and Benefits

- All-in-One Design
- Triple-eye Camera System (3\*50MP)
- High-quality audio pickup experience
- Compatible with Microsoft's MDEP
- Multi-Platform Flexibility
- Simple deployment
- Remote device management

### Ultra HD picture quality and artificial AI features

The MeetingBar A50 has a built-in triple-camera system, each with 50MP resolution—one for wide-angle and two for telephoto, ensuring high-resolution imaging across different focal lengths. The professional-grade lens delivers low grain, natural colors, and HD image quality. It's also a built-in automatic physical privacy shutter that blocks the camera when not in use, ensuring user privacy. The intelligent AI features include IntelliFocus, Multi-stream IntelliFrame with Copilot (only for MTR-W), Video Fence, etc. It can automatically detect speakers in the meeting room, frame them, and display them on the screen through multi-stream output, providing a more intuitive and interactive remote meeting experience.

### High-quality audio pickup experience

Yealink MeetingBar A50 has a 10-meter voice pickup range and built-in stereo speakers, a 16x MEMS microphone array. The intelligent noise reduction technology provides a good audio experience. In addition, it can support 3 additional expansion microphones, which can cover a large conference room.

### Compatible with Microsoft's MDEP

Yealink MeetingBar A50 is compatible with Microsoft's MDEP, which enhances security and deployment experiences. This integration provides users with a more secure environment and streamlined deployment processes, contributing to a smoother and safer user experience.

### Multi-Platform Flexibility

Yealink MeetingBar A50 supports native Teams, Zoom, etc. Additionally, it supports wired General Mode. After entering BYOD mode, you can take MeetingBar A50 as the peripherals for meetings held by third-party apps.

### Simple deployment

Yealink MeetingBar A50 features a direct connection to CTP25, enabling a simplified login process. Only need to

log in once. This streamlined login experience saves users time and enhances convenience.

### Remote Device Management

The Yealink MeetingBar A50 is networked and reported to the device management platform, enabling remote management, configuration, and upgrades.

## Specifications

Parameter	Description
Operating System	<ul style="list-style-type: none"> <li>• Android 13</li> <li>• Based on the Microsoft Device Ecosystem Platform (MDEP)</li> </ul>
Camera	<ul style="list-style-type: none"> <li>• Number of cameras: 3</li> <li>• Number of preset positions: 9</li> <li>• Electronic gimbal</li> <li>• Lens FOV               <ul style="list-style-type: none"> <li>◦ 1x Wide Camera: DFOV 110, HFOV 98°, VFOV 81°</li> <li>◦ 2x Tele Camera: DFOV 51°, HFOV 41.6°, VFOV 31.8°</li> </ul> </li> <li>• Maximum pixels: 3x 50MP pixel</li> <li>• Depth of field: 0.7-8 meters</li> <li>• 8 x digital zoom</li> <li>• Maximum resolution: 3840*2160</li> <li>• Video output resolution: 4k (2160p) 30fps, 1080p60fps</li> <li>• Effective focal length: 8.29 mm (Tele camera), 3.5mm (Wide camera)</li> <li>• Aperture: F/2.0-F/2.4</li> <li>• Supports wide dynamic range</li> <li>• Supports auto exposure</li> <li>• White balance: ATW/auto/manual</li> <li>• Shutter speed: 10ms-33ms</li> <li>• Minimum illumination: 0.5 lux (daytime), 0.1 lux (nighttime)</li> <li>• Privacy cover: Electric lens cap</li> <li>• Lens calibration</li> <li>• Intelligence Features               <ul style="list-style-type: none"> <li>◦ IntelliFocus (4 portraits)</li> <li>◦ Auto Framing</li> <li>◦ Speaker Tracking</li> <li>◦ People Counting</li> <li>◦ Picture in Picture</li> </ul> </li> </ul>

	<ul style="list-style-type: none"> <li>◦ Smart Gallery (Zoom only)</li> </ul>
Speaker	<ul style="list-style-type: none"> <li>• Built-in 4 x 5W speakers <ul style="list-style-type: none"> <li>◦ Rated Power: 4 x 5W</li> <li>◦ Maximum Power: 4 x 10W</li> </ul> </li> <li>• Maximum sound pressure level: 97 dBSPL @ 10 W @ 1 m</li> <li>• Frequency response: 80-20kHz</li> <li>• Sensitivity: 104±3dB 1W/0.1m</li> <li>• Sampling rate: 48khz</li> <li>• Sound emission angle: 0-180°</li> <li>• Total Harmonic Distortion (THD): &lt;3% @1kHz (rated)</li> <li>• Rated impedance: 4ohms</li> </ul>
Microphone	<ul style="list-style-type: none"> <li>• Built-in 16 MEMS microphone array, 10-meter pickup distance</li> <li>• Signal-to-noise ratio: 72dB@1kHz</li> <li>• Maximum sound pressure level: 130dBSPL (whole device), 100dBSPL (individual microphone)</li> <li>• Dynamic range: 22-108dBSPL</li> <li>• Sensitivity: -38dBv/pa</li> <li>• Frequency response: 100-20kHz</li> <li>• Sampling rate: 48kHz</li> <li>• Bit depth: 32-bit</li> <li>• Audio processing: Full duplex, AEC (Acoustic Echo Cancellation), AGC (Automatic Gain Control)</li> <li>• Noise suppression: AI-enhanced noise suppression</li> <li>• Expansion mics: Supports 3 expansion microphones</li> </ul>
Resolution	<ul style="list-style-type: none"> <li>• Lens resolution: Up to 4k30fps</li> <li>• Bandwidth requirement: 10Mbps or more</li> </ul>
Content sharing	<ul style="list-style-type: none"> <li>• Teams: 1080p30fps in meeting, 4k30fps in local sharing</li> <li>Zoom: Up to 1080p30fps</li> <li>• General mode (BYOM): Up to 4k30fps</li> <li>• RingCentral: 1080p30fps</li> <li>• H.323/SIP:1080p30fps</li> </ul>
Video Codec	H.264 High profile, H.264 SVC, H.264
Audio Codec	<ul style="list-style-type: none"> <li>• ARES: 24kHz bandwidth</li> </ul>

	<ul style="list-style-type: none"> <li>• G.722.1C: 16kHz bandwidth</li> <li>• G.722.1: 8kHz bandwidth</li> <li>• G.722: 8kHz bandwidth</li> <li>• G.711 (PCMA/PCMU): 4kHz bandwidth</li> <li>• G.729: 8kHz bandwidth</li> </ul>
Security	<ul style="list-style-type: none"> <li>• Full disk encryption: AES-128, AES-256</li> <li>• Data encryption: symmetric keys, PKI</li> <li>• Device Identity: Protected by device attestation</li> <li>• Device Access: Authenticated using API</li> <li>• Key Protection: Arm TrustZone, RPMP</li> </ul>
Communication standard protocol	<ul style="list-style-type: none"> <li>• H.323/SIP in General Mode (BYOM)</li> <li>• Dual stream protocol: H.239 (H.323) / BFCP (SIP)</li> <li>• FECC: H.224/H.281</li> <li>• H.323 protocol suit: H.245, H.225, H.235, H.241</li> <li>• Gatekeeper account and SIP account</li> </ul>
Network Protocol	<ul style="list-style-type: none"> <li>• Wi-Fi 6 <ul style="list-style-type: none"> <li>◦ 2.4G &amp; 5G dual-band, 802.11a/b/g/n/ac/ax</li> <li>◦ 2x2 MIMO</li> </ul> </li> <li>• Bluetooth 5.0</li> <li>• TCP/IP (IPv4/IPv6), DHCP/static IP</li> <li>• HTTPS secure web access</li> </ul>
Configuration Management	<ul style="list-style-type: none"> <li>• Automatic configuration via web page/display/autoP</li> <li>• Firmware upgrade, factory reset</li> <li>• Configuration import and export</li> <li>• System log export</li> </ul>
Device Management	<ul style="list-style-type: none"> <li>• Yealink Https Web Portal</li> <li>• Yealink Device Management Platform</li> <li>• Yealink Management Cloud Service</li> <li>• Microsoft Device Management Platform (Microsoft Teams Admin Center/Intune)</li> <li>• Zoom Device Management</li> <li>• RingCentral Admin Center</li> </ul>
Installation	<ul style="list-style-type: none"> <li>• Wall Mount (Provided with the product: VB-WallMount-02)</li> <li>• TV Mount (Addition: Purchase VB-TVMount-01, in roadmap)</li> </ul>

	<ul style="list-style-type: none"> <li>• Table Mount (Addition: Purchase VB-TabletopMount-02)</li> </ul>
Ports	<ul style="list-style-type: none"> <li>• 1x USB3.0 Type-A port</li> <li>• 1x USB3.0 Type-B port <ul style="list-style-type: none"> <li>◦ Video output supports formats up to maximum 4k30fps, including 1080p60fps</li> </ul> </li> <li>• 1x USB2.0 Type-C port (for dongle pairing)</li> <li>• 1x Ethernet port: 10/100/1000Mbps</li> <li>• 2x Yealink VCH port (RJ-45)</li> <li>• 1x 3.5mm Line-in &amp; Line-out port</li> <li>• 1x Power port</li> <li>• 1x Security lock slot</li> <li>• 1x Reset slot</li> <li>• 2x HDMI-out <ul style="list-style-type: none"> <li>◦ Video output supports formats up to maximum 4k30fps, including 1080p60fps</li> <li>◦ Supports HDMI CEC</li> </ul> </li> </ul>
Package	<ul style="list-style-type: none"> <li>• MeetingBar A50</li> <li>• Power adapter, 3.5m/11.48ft</li> <li>• HDMI 2.0 cable x2, 1.8m/5.91ft</li> <li>• Network cable x1, 3m/9.84ft</li> <li>• USB3.0 A-B cable x1, 2.5m/8.20ft</li> <li>• Wall mount (VB-WallMount-02)</li> <li>• Table mount (TabletopMount-02)</li> <li>• Cable Cover</li> <li>• MeetingBar A50 Quick Start Guide</li> <li>• Optional package <ul style="list-style-type: none"> <li>◦ A50-010: A50+VCR11</li> <li>◦ A50-031: A50+CTP25 Package (CTP25, 2m/6.56ft 65W PD power adapter, 7.5m/24.6ft Network cable, 1.2m/3.94ft USB C to C cable, High stand, Cable management cover)</li> </ul> </li> </ul>
Environmental Factor	<ul style="list-style-type: none"> <li>• Operating humidity: 10 - 95%</li> <li>• Operating temperature: 0 - 40 °C</li> <li>• Storage temperature: -30°C~70°C</li> <li>• BTU/hr: 38 in idle, 58 in meeting</li> </ul>

Dimensions and weight (W × D × H)	<ul style="list-style-type: none"><li>• MeetingBar A50: 910 × 102 × 88mm</li><li>• N.W/CTN: 8.5kg</li><li>• G.W/CTN: 9.5kg</li></ul>
Warranty	<ul style="list-style-type: none"><li>• Standard: 2-year limited hardware warranty included</li><li>• Extended: Additional extended warranties are available at the time of hardware purchase. Contact your reseller.</li></ul>

## MeetingBar Kit

Meeting Room Type	Model	Kit Contain	Related Topic
Small to Medium Meeting Room	A50-010	MeetingBar A50 VCR11	<a href="#">MeetingBar A50</a>
Small to Medium Meeting Room	A50-031	MeetingBar A50 CTP25	<a href="#">MeetingBar A50</a>

# Yealink CTP25 Datasheet

## Introduction

The CTP25 is a cutting-edge touch console specifically designed for meeting control. With its user-centered interactive design and a 10.1-inch touchscreen, users can effortlessly join and manage meetings with ease. Say goodbye to the complexities of video conferencing as CTP25 simplifies the process, delivering an enhanced meeting experience. It seamlessly integrates essential meeting functions, including direct connection to the system, screen sharing, BYOD, and PD charging capabilities. Elevating communication efficiency to new heights.



Android 13 OS



10.1-inch  
Multi-touch screen



Meeting Control



Connect with Video  
Conference Endpoint



Power over  
Ethernet



One Cable Solution



Wi-Fi & Bluetooth



Ultrasonic



Certified for  
Microsoft Teams

zoom Certified

RingCentral

Built on  
Microsoft Device Ecosystem Platform

## Key Features and Benefits

- 10.1 inches, and ultra-high screen-to-body ratio
- Support Android 13 (continue to update)
- MDEP Supported
- USB-C wired content sharing/BYOD/power
- Ultrasonic technology
- Multiple deployment methods

### Immersive HD Display, Stable Touch

Experience immersive visual excellence with the CTP25. Boasting a 10.1-inch size and a high screen-to-body ratio, this device provides a captivating visual experience. Its IPS panel showcases crystal-clear images, ensuring vibrant and sharp visuals. The IPS hard screen's unique horizontal molecular structure brings exceptional stability, eliminating water ripples, shadows, and flickering when touched. Enjoy seamless touch interactions on the CTP25, where stability and responsiveness combine for an unparalleled user experience.

### Experience Secure MDEP with Android 13

Experience the Latest and Most Secure User Experience with the CTP25. The CTP25 is powered by Android 13 and provides continuous updates, ensuring customers always enjoy the newest features and enhanced security. With compatibility with MDEP (Microsoft Device Ecosystem Platform), the CTP25 provides a more secure environment and streamlined deployment processes. Stay ahead of the curve with the latest updates while enjoying peace of mind knowing your device is protected.

### Flexible Deployment, Powerful USB-C

Enhance your collaboration with the seamless integration of Yealink CTP25 and MeetingBar A40. Simply connect the CTP25 to the MeetingBar A40 using an ethernet cable and enjoy a simplified Teams Room login process. With the option to log in to your Teams account once on either device, deployment becomes effortless, saving time and enhancing convenience. The USB-C cable of CTP25 supports 4K content sharing, wired BYOD (Bring Your Own Device), and provides up to 45w PD2.0 for laptop charging. By replacing the adapter, you can achieve a maximum power output of 60w, catering to higher charging needs. This all-in-one cable solution meets the diverse needs of users in conference rooms, ensuring a streamlined and efficient collaboration experience.

## Specifications

Specifications	Description
OS	<ul style="list-style-type: none"> <li>• Android 13.0</li> </ul>
Display	<ul style="list-style-type: none"> <li>• Screen: 10.1 inch</li> <li>• Display Type: IPS</li> <li>• Resolution: 1280 x 800</li> <li>• Contrast ratio: 1000:1</li> <li>• Brightness: 350 cd/m<sup>2</sup> (typical)</li> <li>• Viewing angle (horizontal/vertical): 178°(H)/178°(V)</li> <li>• Touchpoints: Multi-points capacitive touch support</li> <li>• Anti-glare</li> <li>• Anti-fingerprint</li> </ul>
Audio	<ul style="list-style-type: none"> <li>• Built-in Ultrasound Unit</li> </ul>
Wireless	<ul style="list-style-type: none"> <li>• Wi-Fi 6 802.11a/b/g/n/ac/ax</li> <li>• Bluetooth 5.0</li> </ul>
Network	<ul style="list-style-type: none"> <li>• VLAN, 802.1P/Q, and Diffserv</li> <li>• 802.1X and LLDP-MED</li> <li>• HTTPS</li> </ul>
Device Management	<ul style="list-style-type: none"> <li>• Yealink Web Portal</li> <li>• Yealink Device Management Platform</li> <li>• Teams Admin Center</li> <li>• Zoom Device Management</li> </ul>
Physical Interface	<ul style="list-style-type: none"> <li>• 1 x USB-A port</li> <li>• 2 x USB-C port</li> <li>• 1 x RJ45 port (PoE 802.3af compaint)</li> <li>• 1 x Reset hole</li> <li>• Motion Sensor</li> </ul>
Installation	<ul style="list-style-type: none"> <li>• Place on the Table</li> <li>• Mount on the Table</li> <li>• Mount on the Wall</li> </ul>
Package	<ul style="list-style-type: none"> <li>• CTP25</li> <li>• 7.5m Ethernet Cable</li> <li>• 1.2m USB-C Cable</li> <li>• PD Power Adapter (65W)</li> </ul>

	<ul style="list-style-type: none"> <li>• Screwdriver</li> <li>• High Stand</li> <li>• Cable Management Cover</li> <li>• M3 Screws × 10</li> <li>• Cable Ties × 5</li> <li>• Quick Start Guide</li> </ul>
Mounting Bracket	<ul style="list-style-type: none"> <li>• Standard: High Stand</li> <li>• Optional: <ul style="list-style-type: none"> <li>- Rotatable desktop mount with rotation angle: 90° left and right.</li> <li>- Wall mount</li> </ul> </li> </ul>
Environment	<ul style="list-style-type: none"> <li>• Operating Temperature: -10 to +45°C</li> <li>• Storage Temperature: -30 to +70°C</li> </ul>
Power	<ul style="list-style-type: none"> <li>• Power Consumption: <ul style="list-style-type: none"> <li>- Standby: 5 W</li> <li>- Average: 7.3 W</li> <li>- Peak: 15.2 W</li> </ul> </li> <li>• Power Adapter: 65W PD</li> <li>• PoE: IEEE 802.3af and above</li> </ul>
Dimensions &Weight	<ul style="list-style-type: none"> <li>• Box: <ul style="list-style-type: none"> <li>- Dimension: 286 × 198 × 140 mm</li> <li>- N.W/CTN: 1.578 kg</li> <li>- G.W/CTN: 1.846 kg</li> </ul> </li> <li>• Carton: <ul style="list-style-type: none"> <li>- Dimension: 725 × 410 × 300 mm</li> <li>- N.W/CTN: 18.478 kg</li> <li>- G.W/CTN: 19.798 kg</li> <li>- Quantity: 10 pieces</li> </ul> </li> <li>• CTP25: <ul style="list-style-type: none"> <li>- Dimension: 242.95 × 27.50 × 161.95 mm</li> <li>- Weight: 0.683 kg</li> </ul> </li> </ul>