



**Full duplex HD IP Conference Phone** 

- **Power over Ethernet**
- 3 metre range and 360 degree voice pickup
- 5 way conference
- **USB** call recording
- PC audio connection
- **Optional expansion microphones**



# HD SIP Conference Phone enhances collaboration and improves productivity

conferencing

/ PC port

microphones kit

recording

The Yealink CP860 IP Conference phone is the perfect choice for any business needing to communicate with dispersed teams, customers, partners and suppliers. Ideal for small and medium-sized conference rooms, the phone can be used for up to 16 people when using the optional expansion microphones. The Yealink CP860 benefits from optima HD technology, 3 built-in microphones, fully duplex and acoustic echo cancelling providing a rich and clear audio experience. In addition the CP860 supports call recording when utilising a USB flash drive.

HD Voice



CP860/MAR15/1



**CP860** Accessories

Microphone Expansion Kit Optima HD Voice Full duplex technology Echo cancellation

3 metre range and 60 degree voice pickup Mute function via touchpad

#### **Audio Features**

Optima HD voice 3-metre microphone pickup Built in 3 microphone arrray, 360 degree vocie pickup 112 mm diameter and 2.7w speaker Full-duplex speakerphone with AEC Echo cancellation tail length is up to 400ms Reverberation elimination Background noise suppression Codecs: G.722, G.711(A/µ), G.729AB, iLBC DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO

### VAD, CNG, PLC, AJB, AGC

#### **Phone Features**

1 VoIP account Call hold, mute, DND Call recording, hotline 5-way conference calls Redial, call waiting, emergency call Call forward, call transfer, call return, dial plan Ring tone selection/import/delete Set date time manually or automatically Volume adjustment

#### Directory

Local phonebook up to 1000 entries XML/LDAP remote phonebook Intelligent search method Phonebook search/import/export Call history: dialled/received/missed/ forwarded Black list

#### **IP-PBX Features**

Intercom, multicast paging Anonymous call, anonymous call rejection Voice mail, distinctive ringtone, call pickup

#### Display

192x64-pixel graphical LCD with backlight 24 total keys: 4 softkey, off-hook key, on-hook key, redial, mute, volume key, 3 navigation keys Phone lock National language selection Caller ID with name, number LCD display logo

#### Interface

1xRJ45 10/100M Ethernet port Power over Ethernet (IEEE 802.3af ), class 0 2xEX mic port 1xUSB2.0 port 1xmobile phone/PC port: 3.5mm 1xSecurity lock port

#### Network and security

SIP v1 (RFC2543), v2 (RFC3261) SIP server redundancy supported IPv4/IPv6 NAT traverse: STUN mode Proxy mode and peer-to-peer SIP link mode IP assignment: static/DHCP HTTP/HTTPS web server Time and date synchronization using SNTP UDP/TCP/DNS-SRV(RFC 3263) QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP SRTP for voice encryption Transport Layer Security (TLS) HTTPS certificate manager AES encryption for configuration file Digest authentication using MD5/MD5sess OpenVPN, IEEE802.1X

#### Management

Setup wizard Configuration: browser/phone/autoprovision Auto provision via FTP/TFTP/HTTP/ HTTPS for mass deploy Auto-provision with PnP Zero-sp-touch, TR-069, SNMP Reset to factory, reboot Package tracing export, system log

#### Other physical features

4 context-sensitive "soft" keys External universal AC adapter (optional): AC 100~240V input and DC 5V/2A Output Power consumption (PSU): 2.8-5.6W Power consumption (PoE): 4.0-8.2W Dimension(W\*D\*H): 320mm\*260m\*52mm Operating humidity: 10~95% Storage temperature: -10~50°C


#### Certifications



WEEE Compliant

**ROHS** Compliant





## Yealink

Yealink (UK) Ltd, Pennine House, Salford Street, Bury, Lancashire, BL9 6YA, United Kingdom Tel: +44 (0)161 763 2060 Email: sales@yealink.co.uk Web: www.yealink.co.uk

© 2015 Yealink (UK) Ltd. All rights reserved. Information contained in this document is subject to change without notice.