Yealink

Professional IP Phone Compatible with Microsoft® Skype for Business

The T41P SFB desktop phone is compatible with Microsoft® Skype for Business and includes conferencing, Boss/Admin, Common Area Phone and Calendar in Outlook. The wireless "Better Together over Ethernet" (BToE) feature enables seamless switching between Skype for Business desktopclient and T41P phones. Thanks to its Optima HD Voice technology, users enjoy conversations in lifelike, crystalclear audio.









Optima Wire HD Voice BTo

Key Features and Benefits

Optima HD Voice

A combination of software and hardware, together with the implementation of wideband technology maximize the T41P SFB's acoustic performance. Advanced acoustic clarity technology including full duplex, echo cancellation and adaptive jitter buffer - come together for an amazing face-to-face live experience.

Maximize Productivity

The T41P SFB is fully compatible with Skype for Business online, on-premises and hybrid deployment- effectively extending the benefits of Microsoft® Skype for Business. Pin your favourite contacts directly to the home screen, visually arrange them as you like, and dial them easily with just a tap. The T41P SFB lets users synchronize Outlook Calendar meeting schedules in real-time- by simply clicking to join a meeting. The T41P SFB is further outfitted with directory synchronization, visual voicemail management, Boss/Admin and more- raising the bar for productivity to new heights.

Effortless Deployment

Supporting Microsoft's Skype for Business Server in-band provisioning and in-band configuration management enables a carefree configuration and easier-than-ever mass deployment. Automatically deploy on a variety of servers- http, https, tftp and ftp.

- 2.7" 192x64 pixel backlit LCD
- Modern Skype for Business User Interface
- Intelligent Directory Search
- Synchronised Outlook Calendar with meeting "Join" feature
- Common Area Phone
- Boss/Admin support
- PoE support
- Headset Electronic Hook Switch (EHS) support

Microsoft Partner Gold Communications

Exclusive Yealink UK
LIFETIME WARRANTY



T41P SFB

Audio features

- Optima HD voice: HD handset, HD speaker
- Full-duplex hands-free speakerphone with AEC
- Codecs: G.722 (Wideband), G.711 (A/μ), G.723, G.729AB, G.726, GSM, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- VAD, CNG, AEC, PLC, AJB, AGC

Directory

- Contacts synchronize with client
- View SFB contacts and their current presence status
- Support local contacts
- Support Global search, Compatible with exchange
- · Smart dialing
- Call history: placed/received/missed/forwarded

Signing into Microsoft SFB

- Sign in: PIN Authentication/User credentials
- Signing in via BToE
- Signing in via web user interface
- Auto root certificate fetch

BToE features

- Click to call/Click to answer
- Audio device switch from IP Phone to PC
- wireless pairing with PC client
- As a PC Audio device

Phone features

- Presence status synchronize with client
- Reset presence status, Privacy mode
- · Phone Lock
- Favourite contacts sorting
- Favourite contacts click to call
- Call hold, call waiting, redial, mute
- Branch office support
- Support Group call pickup

- · Call forward, call transfer, call park
- SFB conferencing (Microsoft CCCP)
- Boss/Admin function
- Common Area Phone (CAP)
- · Calendar function, Outlook meeting schedules synchronization
- · Paging, Music on hold
- E911, Federation, Response group, Private line
- Ring tone selection/import/delete
- Dial plan
- Visual voicemail
- Message waiting indicator (MWI)
- Volume adjustment

Interface

- 2xRJ45 10/100M Ethernet ports
- Power over Ethernet (IEEE 802.3af), class 2
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Display and indicator

- 2.7" 192 x 64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- National language selection
- Caller ID with name, number
- Presence status control: available, busy, DND, be right back, off work, appear away

Network and security

- SIP v1 (RFC2543), v2 (RFC3261)
- IPv4/IPv6
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP/PPPoE
- DNS Assignment: Static/DHCP
- · HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP

- · SRTP for voice
- Transport Layer Security (TLS)
- EWS authentication
- HTTPS certificate manager
- Digest authentication using MD5/MD5-sess
- IEEE802.1X

Management

- Configuration: browser/phone/Auto provisioning
- Auto provisioning: RPS/In-band provisioning
- In-Band Configuration Management
- QoE (Monitoring Reports)
- Single identity (active directory)
- Media Bypass
- Firewall Traversal
- Reset to factory, reboot
- Package tracing export, system log
- · Screenshot via URL
- · Phone log click to upload
- · View License status

Other physical features

- External universal AC adapter (optional): AC $100 \sim 240 \text{V}$ input and DC 5 V/1.2 A output
- Power consumption (PSU): 1.4~3.9W
- Power consumption (PoE): 2.1~5.9W
- Dimension (W*D*H*T): 212mm*189mm*175mm*54mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

Package features

- Qty/CTN: 5 PCS
- N.W/CTN: 6.4 kg
- G.W/CTN: 7.0 kg
- Giftbox size: 246mm*223mm*120mm
- Carton Meas: 627mm*256mm*235mm

Certification













